

LIQUID TRANSFER TANKS



Steel Vertical



Steel L-Shape



Steel Rectangular



Steel Square



Aluminum Rectangular



HEAVY-DUTY INDUSTRIAL TRANSFER TANKS



Transfer tanks make it easy to transport non-flammable liquid to on-site vehicles and equipment. All tanks are 100% quality inspected with a dual pressure and submersion leak test prior to leaving the factory. The transfer tanks have baffles to add strength while preventing contents from shifting. - Flush mounted dual 2 In. reinforced bungs - Constructed of 12 guage steel or non-rusting .125 diamond tread plate aluminum. Overfill restriction allows for automatic shut-off at the pump and the lockable cap and coupler allow venting.- Mounting kit included - Baffles add strength while preventing contents from shifting.

DESCRIPTION	ALUMINUM	STEEL	LENGTH	WIDTH	HEIGHT
200 Gallon Rectangular Tank		37224244	62"	28"	28"
150 Gallon Rectangular Tank		37224243	48"	28"	28"
100 Gallon Rectangular Tank	37024151	29224164	45.25"	24"	24"
100 Gallon L-Shape Tank	37024149	29224167	59"	31"	24"
88 Gallon L-Shape Tank	37024150	29224163	54.25"	31"	24"
75 Gallon L-Shape Tank	37024158		48.25"	31"	24"
75 Gallon L-Shape Tank		29224162	43.50"	31"	24"
50 Gallon Square Tank	37024152	29224165	24"	24"	24"
36 Gallon Vertical Tank	37024153	29224166	48.25"	11"	24"
75 Gallon Combo Tank	37024159	29224168	48.25"	31"	24"



Aluminum L-Shape



Aluminum Vertical




Aluminum Square



#FRTC 2" Vented Fuel Tank Cap

#2420200 Fuel Cap & Bung
4 1/4" x 2 3/4" x 2 3/4"



UWS

75 & 85 Gallon Aluminum Tank / Toolbox Combination

#TT-75-COMBO 75 Gallon Tank

#TT-85-COMBO 85 Gallon Tank



48 x 27 x 24 inches

The UWS 75 and 85 gallon combo transfer tanks are a storage solution for working pickup trucks that is designed to simultaneously transport non-flammable liquids, and tools. The unit consists of an L-shaped transfer tank, with a single-lid tool chest welded to the inner angle of the tank. Additional features include: dual-grade durable aluminum construction, a vented tank cap, compatibility with a variety of pumps (sold separately), internal tank baffles, an insulated gas strut controlled lid, a beveled and notched chest design, dual locking chest paddle handles and integrated mounting flanges.

LIQUID TRANSFER PUMPS



Model# 1210G

FILL-RITE HEAVY-DUTY FUEL TRANSFER PUMPS

FILL-RITE

12 VOLT, 15 GPM, MODEL# 1210G

PART NO. DESCRIPTION

1210G 12 Volt, 15 GPM Fuel transfer pump, , 12' Hose, HD Switch
Fill-Rite Fuel Transfer Pump is an industry-standard, contractor-grade pump featuring an explosion-proof motor with permanent magnet. The 15 GPM rating allows for quick, convenient fuel transfer every time, even in cold conditions. The steel suction pipe telescopes from 22in. to 33 3/4in. to fit a variety of in-bed truck tanks. UL listed Motor. U.S.A.



Model# 4210D

12 VOLT, 20 GPM, MODEL# 4210D

FILL-RITE

PART NO. DESCRIPTION

4210D 12 Volt, 20 GPM Fuel transfer pump, 12' Hose, HD Switch
4210DBFQ 12 Volt, 20 GPM Fuel transfer pump, 20' Hose, Filter & Auto-Nozzle
Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. Steel suction pipe telescopes from 22in. to 40in. Features built-in check valve and strainer, hose with static ground wire and thermal overload protection. Padlockable. UL listed. U.S.A.



Model# 610c

115 VOLT, 15 GPM, MODEL# 610C

FILL-RITE

PART NO. DESCRIPTION

610C 115 Volt, 15 GPM Fuel transfer pump
Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. Steel suction pipe telescopes from 22in. to 40in. Features built-in check valve and strainer, hose with static ground wire and thermal overload protection. Can be mounted to a 55-gallon drum. Padlockable. UL listed. U.S.A.



Model# 152

HAND FUEL PUMP — 2IN. NPT, MODEL# 152

FILL-RITE

PART NO. DESCRIPTION

152 Hand Fuel Pump — 2in. NPT
Easy-to-use Fill-Rite pump features anti-siphoning device, built-in inlet strainer and easy-grip handle. Suction pipe adjusts for 15- to 55-gallon drums. Includes nozzle with protective boot and 8ft. static wire hose. No foot valve required. U.S.A.



Model# 112

ROTARY HAND PUMP, MODEL# 112



FILL-RITE


PART NO. DESCRIPTION

112 Hand Fuel Pump — 2in. NPT
Cast aluminum Fill-Rite pump provides smooth, continuous transfer of medium viscosity liquids, as well as oil, gasoline and diesel fuel. Improved seal keeps water out. Built-in check valve and strainer. Pump easily mounts to a standard drum with 2in. NPT. Anti-siphoning device, hose with static wire and a 22in. to 40in. telescoping suction pipe. Padlockable pump can be set up for reverse flow and is adaptable for drums, kegs or storage tanks. U.S.A.

FILL-RITE PUMPS • SERVICE AND ACCESSORIES

FILL-RITE

	PART #	DESCRIPTION
	NOZZLES NO75DAU10	3/4" Auto Nozzle w/Hook, Diesel Spout
	N075UMIN11	3/4" Inlet, 1" Spout, Manual Nozzle
	N100DAU10	1" Auto Nozzle with Hook - Diesel
	N10UMN11	1" Manual Nozzle
	700H0079	Clips, Screws for Green Handle Nozzles
	4200F9111	Nozzle Hook
PIPING	1200KTG9099	1" Steel Telescoping Pipe (20" to 34-3/4")
	HOSES 700F3135	3/4" X 12 Ft. Hose
	FRH10012	1" X 12 Ft. Hose w/Spring Guard
	FRH10020	1" X 20 Ft. Hose w/Spring Guard
SWIVELS	S034H1311	3/4" Single Plane Swivel
	S100H1312	1" Single Plane Swivel
	S075H1314	3/4" Multi-Plane Swivel
	S100H1315	1" Multi-Plane Swivel

	PART #	DESCRIPTION
METERS	807CMK	Meter Kit for 700/1200 Models - 3/4" NPT
	901MK4200	Meter Kit for 1" thread NPT pumps
	FILTERS 1200KTF7019	Particulate Filter Kit - 100/5200/1200 Series
	1200KTG9075	3/4" Cast Filter Head - 100/5200/1200 Series
	1810PM1	Canister Filter w/Drain - 100/5200/1200 Series
	F1810HM0	Hydrosorb Element - Fits 1200KTF7019 Kit
	F1810PCI	Filter Head & Canister, 120PSI, 3/4" Out
	F4010PM0	Particulate Element - Fits 1Inch Filter Head
	700ACCF7017	1 Inch Aluminum Filter Head
REPAIR	4200KTF8739	Repair Kit - Fits 1210C / 4200D
WIRING	1200R9067	18" Two Wire Cable
	1200F3170	Lineswitch - 1200 Series
CAPS	FRTC	Replacement Fuel Tank Cap Only
	2420200	Replacement Cap & Bung