

# PINTLE HOOKS / COMBO HITCHES / MOUNTS



## PINTLE HOOK MOUNTS

- Converts receivers for use with pintle-type trailers, quickly and easily
- Provides mounting for both ball and pintle and rigid type pintle hooks
- Pin and clip must be ordered separately



Part No.	Shank	Rating (lbs.) GTW/TW	A Shank	B Length	H Shank Dia.	C Height	D Width	E Hole	F Width	G Height	Hole Sets
63056	Hollow	6,000/600	7-5/8"	3"	2"	5-1/2"	5"	17/32"	3-3/8"	1-3/4"	3
63057	Solid	12,000/1,200	7-5/8"	3-1/4"	2"	7-1/2"	5"	17/32"	3-3/8"	1-3/4"	4
PM84	Solid	20,000/4,000	6-1/2"	2-5/8"	2"	7-3/8"	5"	17/32"	3-3/8"	1-3/4"	2
PM87	Solid	10,000/2,000	6-1/2"	2-5/8"	2"	7-3/8"	5"	17/32"	3-3/8"	1-3/4"	4
PM107	Solid	10,000/2,000	7-3/4"	2-5/8"	2"	7-3/8"	5"	17/32"	3-3/8"	1-3/4"	4
63059	Solid	12,000/1,200	11-3/8"	3-1/4"	2"	7-1/2"	5"	17/32"	3-3/8"	1-3/4"	4
PM812	Solid	10,000/2,000	9-5/8"	2-5/8"	2"	12-1/2"	5"	17/32"	3-3/8"	1-3/4"	7
PM1012	Solid	10,000/2,000	11-3/4"	2-5/8"	2"	12-1/2"	5"	17/32"	3-3/8"	1-3/4"	7
45156 <sup>†</sup>	Hollow	12,000/1,200	7-3/4"	3-1/4"	2-1/2"	6"	5"	17/32"	3-3/8"	1-3/4"	3
45294 <sup>†</sup>	Forged	18,000/2,000	8-1/2"	3-1/4"	2-1/2"	7-1/4"	5"	17/32"	3-3/8"	1-3/4"	4

<sup>†</sup> Titan® pintle hook adapter mount



## PINTLE HOOKS



Part No.	Description
PH5	5 Ton, 2,000 lbs. max. vertical load, 10,000 lbs. GTW
63014	10 Ton, 4,000 lbs. max. vertical load, 20,000 lbs. GTW, with Mounting Hardware
PH15	15 Ton, 6,000 lbs. max. vertical load, 30,000 lbs. GTW
PH20	20 Ton, 8,000 lbs. max. vertical load, 40,000 lbs. GTW
PH30	30 Ton, 15,000 lbs. max. vertical load, 60,000 lbs. GTW
PH45	45 Ton, 16,000 lbs. max. vertical load, 90,000 lbs. GTW
B8520	PH5, PH15 Hardware Mounting Kit
B8525	PH20 Hardware Mounting Kit
B8530	PH30, PH45 Hardware Mounting Kit



## PINTLE HOOK COMBINATION HITCHES

Part No.	Description
BH81780	1-7/8" Combo Hitch, 3000 lbs. Max Vert. Load, 16,000 lbs. GTW, ball rating 6,000 lbs.
BH82000	2" Combo Hitch, 3000 lbs. Max Vert. Load, 16,000 lbs. GTW, ball rating 10,000 lbs.
BH82516	2-5/16" Combo Hitch, 3000 lbs. Max Vert. Load, 16,000 lbs. GTW, ball rating 14,000 lbs.
BH102000	2" Combo Hitch, 4,000 lbs. Max Vert. Load, 20,000 lbs. GTW, ball rating 10,000 lbs.
BH102516	2-5/16" Combo Hitch, 4,000 lbs. Max Vert. Load, 20,000 lbs. GTW, ball rating 14,000 lbs.
B8520	BH81780, BH82000, BH82516 Hardware Mounting Kit
B8525	BH102000, BH102516 Hardware Mounting Kit



## PINTLE HOOK REPLACEMENT PARTS

Part No.	Description
RB1780	BH81780 1-7/8" Replacement Ball, 6,000 lbs., 1-1/4" diameter
RB2000	BH82000 2" Replacement Ball, 10,000 lbs., 1-1/4" diameter
RB2516	BH82516 2-5/16" Replacement Ball, 14,000 lbs., 1-1/4" diameter
RB102000	BH102000 2" Replacement Ball, 10,000 lbs., 1-1/4" diameter
RB102516	BH102516 2-5/16" Replacement Ball, 14,000 lbs., 1-1/4" diameter
P11C	Replacement Snapper Pin, 1/4"
B8520	BH81780, BH82000, BH82516 Hardware Mounting Kit
B8525	BH102000, BH102516 Hardware Mounting Kit

# PINTLE HOOKS / LUNETTE EYES



BP100A

BP125A

BP200

BP760A

BP880



RM5P

RM67180

5761/5762



5763/5764



BDB125015

BDB1385

BDB12503

BDB12492H

B18128  
Assembly

B16137

B16140

LW10

BDL253

## FORGED SWIVEL-TYPE PINTLE HOOKS



Part No.	Description
<b>BP100A</b> 15 Ton	6,000 lbs. MVL, 30,000 lbs. MGWTW Spring cushion swivel action provides torsion relief 2-3/8" to 3" I.D. with 1-1/4" to 1-5/8" diameter section. Recommended for off-road
<b>BP125A</b> 15 Ton	6,000 lbs. MVL, 30,000 lbs. MGWTW Spring cushion swivel action provides torsion relief 2-3/8" to 3" I.D. with 1-1/4" to 1-5/8" diameter section. Recommended for off-road
<b>BP200</b> 25 Ton	6,000 lbs. MVL, 50,000 lbs. MGWTW Spring Cushion Swivel action provides torsion relief 2-3/8" to 3" I.D. with 1-1/4" to 1-5/8" diameter section. Recommended for off-road
<b>BP760A</b> 30 Ton	12,000 lbs. MVL, 60,000 lbs. MGWTW Spring Cushion Swivel action provides torsion relief 3" I.D. with 1-5/8" diameter section. Recommended for off-road
<b>BP880</b> 50 Ton	20,000 lbs. MVL, 100,000 lbs. MGWTW Spring Cushion Swivel action provides torsion relief 3" I.D. with 1-5/8" diameter section. Recommended for off-road

## ONE-PIECE PINTLE HOOK



Part No.	Description	Max GTW	Ball GTW	Max VL
<b>RM5P</b>	5-Ton Receiver Mount Pintle Hook	10,000	-	2,000

## ONE-PIECE PINTLE COMBINATIONS

Part No.	Description	Max GTW	Ball GTW	Max VL
<b>RM67180</b>	1-7/8" Receiver Mount Pintle Combination	12,000	2,000	2,400
<b>RM62000</b>	2" Receiver Mount Pintle Combination	12,000	7,000	2,400
<b>RM62516</b>	2-5/16" Receiver Mount Pintle Combination	12,000	12,000	2,400

## CLEVIS MOUNTS

• For use with industrial/agricultural equipment

Part No.	Description	Ball Mount GTW/TW (lbs.)	Clevis Mount GTW/TW (lbs.)	Length
<b>5761</b>	Clevis Mount, 3/4" hole	3,500/350	5,000/350	9-3/4"
<b>5762</b>	Clevis Mount, 1" hole	6,000/600	6,000/600	8-7/8"
<b>5763</b>	Clevis Pin, 3/4" dia.			4-1/4"
<b>5764</b>	Clevis Pin, 1" dia.			4-3/4"

## LUNETTE RINGS



Part No.	Description
<b>BDB125015</b>	Lunette Ring, 2-1/2" dia., 4 hole base 35,000 lbs. GTW
<b>BDB1385</b>	Lunette Ring, 2-1/2" dia., 4 hole base 60,000 lbs. GTW
<b>B8520</b>	Hardware Mounting Kit for BDB125015, BDB1385
<b>BDB12503</b>	Lunette Ring, 2-1/2" dia., 1-1/2" shank 15,000 lbs. GTW
<b>BDB12492H</b>	Lunette Ring, 3" dia., 1-5/8" shank 45,000 lbs. GTW
<b>B18128</b>	Adjustable Eye Assy. with <b>3-position steel channel</b> Ductile cast iron eye • 3" I.D. eye, 1-9/16" eye section Eye Capacity: 2,000 lbs. M.V.L., 14,000 lbs. M.G.T.W.
<b>B18135</b>	Adjustable Eye Assy. with <b>5-position steel channel</b> Ductile cast iron eye • 3" I.D. eye, 1-9/16" eye section Eye Capacity: 2,000 lbs. M.V.L., 14,000 lbs. M.G.T.W.
<b>B16137</b>	Adjustable Eye Only - <b>7 Ton</b> Ductile cast iron eye • 3" I.D. eye, 1-9/16" eye section Eye Capacity: 2,000 lbs. M.V.L., 14,000 lbs. M.G.T.W.
<b>B16140</b>	Adjustable Eye Only - <b>10 Ton</b> Ductile cast iron eye • 3" I.D. eye, 1-9/16" eye section Eye Capacity: 2,000 lbs. M.V.L., 20,000 lbs. M.G.T.W.
<b>B8978</b>	3 Position Channel Only
<b>B8979</b>	5 Position Channel Only with Weld Gussets
<b>B9020</b>	Bolt & Nut Kit for Adjustable Eye Assemblies
<b>LW10</b>	Lunette Ring, Weld-On, 2-1/2" Diameter
<b>BDL253</b>	Lunette Ring Lock