

TRAILER WINCHES



Fulton brand single speed winches are designed to meet your toughest pulling demands. They feature efficient gear ratios, full-length drum bearings, oil-impregnated shaft bushings, and our "Comfort Grip" handle for ease of cranking. All gears are high-carbon steel for superb strength. Zinc finishes provide excellent corrosion resistance in all environments. All models are designed for use with rope or strap.



SINGLE SPEED TRAILER WINCHES

Part No.	Capacity	Gear Ratio	Handle Length	Max. Mech. Adv**	Ratchet Type	Drum Storage			Strap Mfg. Bolt Sizes (Not Included)	Replace Handle	Strap Included	Packaging
						Rope	Cable	Strap				
T600 0101	600	3.1:1	6"	34:1	Two-way	36' x 1/4"	N/A	15' x 2"	1/4" x 2-1/2" Grade 5	5868	NO	Litho Box
T900 0101	900	3.1:1	7"	39:1	Two-way	36' x 1/4"	N/A	15' x 2"	1/4" x 2-1/2" Grade 5	6312	NO	Bulk
T1300 0101	1,300	4.1:1	8"	49:1	Two-way	30' x 5/16"	N/A	20' x 2"	1/4" x 2-1/2" Grade 5	6302	NO	Litho Box

CE All Cequent Performance Products single speed trailer winches are **CE** compliant. **Maximum Mechanical Advantage - Based on first layer of recommended line on the drum. For maximum efficiency, use only the amount of line required.



The F2® Winch addresses the need for attractive design in every element of a marine trailer. It complements the look of even high end boat and trailer combinations and continues the industry changing improvements in both performance and style of the Fulton F2® series of products.



F2® TRAILER WINCHES

Part No.	Capacity	Gear Ratio	Handle Length	Strap	Strap Included	Mounting Hardware Included	Finish	Packaging	Unit Wt. Lbs.
F2® SINGLE SPEED TRAILER WINCH									
FW16000101	1,600	4.1:1	2 Position 6", 7"	20' x 2" w/Hook	YES	YES	Sharkskin™	Display Box	9.25
FW20000101	2,000	5.1:1	4 Position 6", 7", 8", 9"	20' x 2" w/Hook	YES	YES	Sharkskin™	Display Box	6.7



Make light work of heavy loads with Fulton brand two-speed winches. One fast speed for quick pull-in, a second low speed for increased mechanical advantage. Our shift lock design allows changing gears without moving the crank handle from shaft to shaft. Just lift the shift lock and slide the shaft into the desired gear position. Shift lock holds the shaft in gear. Neutral, free-wheel position allows quick line pay out without spinning the handle.



TWO SPEED TRAILER WINCHES

Part No.	Cap.	Gear Ratio	Handle Length	Max. Mech. Adv**	Ratchet Type	Drum Storage		Strap Mfg. Bolt Sizes (Not Included)	Hub Size	Hand Brake	Replace Handle	Strap Includ.	Cable Includ.	Pkg.
						Cable	Strap							
T2005 0101	2,000	4.1:1 & 9.8:1	10"	87:1	Two-way w/neutral	N/A	20' x 2"	N/A	1"	1619-01***	6817	NO	N/A	Litho Box
T2605 0301	2,600	5.1:1 & 12.2:1	10"	108:1	Two-way w/neutral	N/A	20' x 2"	N/A	1"	1619-01***	6817	YES	N/A	Bulk
T3205 0101	3,200	5.1:1 & 12.2:1	10"	79:1	Two-way w/neutral	100' x 7/32"	N/A	Cable only	1-3/4"	1619-01***	6817	N/A	NO	Litho Box
T3700 0101	3,700	5.1:1 & 12.2:1	10"	102:1	Two-way	90' x 7/32"	N/A	Cable only	1-3/4"	Included	9235	N/A	NO	Litho Box

Only winches that are shown to accommodate steel cable should be used with steel cable. Cable keeper kits are included with the winches specifying steel cable. Winches rated for steel cable have a larger drum hub to reduce or lessen chance of kinking or fraying.



WORM GEAR WINCHES



Part No.	Capacity	Description	Gear Ratio	Drum Cable Storage				Drum Diameter	Drive
				1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6.5 mm)	5/16" (7.9 mm)		
KW20000103	2,000 lbs. 907 kg	Regular drum Handle drive	31:1	235' (71 m)	100' (30 m)	—	—	1.5" (38.1 mm)	8" handle (20.3cm)

WINCH STRAPS AND CABLES

Part No.	Description	Packaging
WS20 0200	Winch Strap and Hook - Nylon web winch strap with hook, 2" x 20', 2,600 lb. maximum working load	Bulk
WC325 0100	Winch Cable and Hook - 3/16" x 25' galvanized cable, 4,200 lb. breaking strength	Clam Shell
WC750 0100	Winch Cable and Hook - 7/32" x 50' galvanized cable, 5,600 lb. breaking strength	Bagged



POWER WINCHES



1125220

TERRA SERIES

All Terra winches come standard with a steel drum specifically designed to withstand the rigors of synthetic rope (a Superwinch Exclusive). The heavy duty permanent magnet motor includes larger diameter wire within the winding (nearly twice as thick as the competition) and sealed bearings at both ends of the motor. This is the industry's first truly sealed ATV winch assembly. All seals on the entire winch, from the outermost end of the motor to the ergonomic Free-Spooling control knob, exceed the IP67 rating. Even the handlebar-mounted rocker switch, the 10' hand-held remote, and the solenoid are sealed to meet tough standards, which ensures water, mud, snow, and dust is kept out.



1220200

T SERIES

This is the Original T Series Winch that started the small, compact winch segment over 15 years ago; the most copied winch in the world! Full metal planetary gear train, heavy duty rocker switch (the best in the industry), mechanical and dynamic brake (the copy cats leave these out) and 50' x 5/32" wire rope with a latched hook. Includes HD rocker switch.



1323200

GP SERIES

This compact winch is rated at 2,300 lbs line pull with 60' of wire rope, mechanical and dynamic braking, pulley block and contains the S3™ solenoid, the best solenoid in the winch market. It contains the S3™ solenoid, the best solenoid in the winch market with the only 3-Year Warranty, the best solenoid warranty in the industry! Includes 15' hand-held remote.

1330200



1430200
1440200
1450200

S SERIES

The S Series is from Superwinch, the most popular performance trailer winches on the market. With race proven reliability, S Series winches have full metal gears, powerful motors, and a rugged hand-held remote. Full metal gears deliver power and performance. Hand-held switch on 30' of rubber cord is included. Instant stop design ensures absolutely no coasting. Lever operated clutch simplifies fast wire rope payout, metal can style solenoid, and a 1.3 hp motor. Other standard features include power IN and OUT, free-spooling drum, mechanical and dynamic braking, and roller fairlead. The fully enclosed housing helps keep the weather out. They call these winches "The Racer's Choice!"



1910C

X9 SERIES

With its rugged and long lasting differential planetary gearbox, the Superwinch X9 ensure years of dependable service. The "dual" solenoid system can be mounted directly on the winch or can be remotely mounted for remote access. The Superwinch X-9 is so tough, it's the Original Equipment winch for the Toyota HiLux, LandCruiser 70, LandCruiser 200 and the Prado in Australia for over 10 years. Equipped with a powerful electric motor and a compact, heavy duty solenoid unit, the Superwinch X9 delivers up to 9000lb (4082kg) pulling capacity, while its durable, rubberized hand remote control with water proof toggle switch is designed for safe and dependable operation. If you want a winch to perform in your "Outback", the X-9 is the the winch for your vehicle!

Quick Connects



2224 Kit

Pulley Blocks

Roller Fairleads

Wiring Kits

POWER WINCHES

Part No.	Pull Rating	Motor	Gearing	Brake	Rope	Hook	Fairlead	Dimensions
1220200	2,000 lbs	0.71 HP	153:1	Mechanical	Wire Rope 5/32" x 50'	Latched	Roller	12.5" L x 3.9' D x 4.1" H
1323200	2,300 lbs	0.71 HP	153:1	Automatic	Wire Rope 5/32" x60'	Latched	Roller	12.5" L x 3.9' D x 4.1" H
1125220	2,500 lbs	1.3 HP	140:1	Automatic	Wire Rope 3/16" x 50'	HD Clevis	HD 4-Way	3.2" L x 4.5' D x 4.8" H
1330200	3,000 lbs	1.1 HP	153:1	Mechanical	Wire Rope 3/16" x 50'	Latched	Roller	12.7" L x 4.5' D x 4.6" H
1430200	3,000 lbs	1.3 HP	159:1	Mechanical	Wire Rope 3/16" x 60'	Latched	4-Way	15.1" L x 8.7" D x 6.0" H
1440200	4,000 lbs	1.8 HP	159:1	Mechanical	Wire Rope 7/32" x 60'	Latched	4-Way	15.1" L x 8.7" D x 6.0" H
1450200	5,000 lbs	2.1 HP	159:1	Mechanical	Wire Rope 1/4" x 50'	Latched	4-Way	15.1" L x 8.7" D x 6.0" H
1901C	9,000 lbs	4.2 HP	253:1	Automatic	Wire Rope 5/16" x 100'	HD Clevis	HD 4-Way	22.88" L x 6.75" D x 6.63"

WINCH ACCESSORIES

Part No.	Description
1505	Vinyl Winch Cover Fits X3, X3F, S3000, S4000, and S5000 winches
1520	Trailer Wiring Kit for EX1, X1, X2, X3, S3000, and S4000 Series Winches
1535	Wire Rope 5/32" x 25' (3.9mm x 7.6m)
1551	Quick Connects 6-10 AWG
1560A	Roller Fairlead – Fits EX1, X1, X2, and X3
1567	Controller - Fits various units
2007	Front Wiring Kit Fits Models 5,000 – 16,500 lbs capacities with 5' Lead

WINCH ACCESSORIES

Part No.	Description
2008	Trailer Wiring Kit for S5000, S6000, S9000, X9
2224	Kit contains Swing Away Pulley Block - 20,000 lbs, two 3/4" Bow Shackles, Nylon Strap & gloves
2227A	Pulley Block for winches rated up to 8,000 lbs.
2229A	Pulley Block for winches rated up to 10,000 lbs
2236	Quick Connects 2- 4 AWG
2270	Hand-Held Switch 15' for the GP Series, EP Series, Husky Series, S6000/9000 and X6/9 winches.
2349	HD Roller Fairlead Kit Fits ATV winches
2549	HD Roller Fairlead Kit Fits X6, X9, S6000, and S9000