

# TRAILER WINCHES



Fulton brand single speed winches are designed to meet your toughest pulling demands. They feature efficient gear ratios, full-length drum bearings, oil-impregnated shaft bushings, and our "Comfort Grip" handle for ease of cranking. All gears are high-carbon steel for superb strength. Zinc finishes provide excellent corrosion resistance in all environments. All models are designed for use with rope or strap.



## SINGLE SPEED TRAILER WINCHES

Part No.	Capacity	Handle Length	Max. Mech. Adv**	Drum Storage			Strap Mfg. Bolt Sizes (Not Included)	Replace Handle	Strap Included	Packaging
				Rope	Cable	Strap				
142001	900	7"	39:1	36' x 1/4"	N/A	15' x 2"	1/4" x 2-1/2" Grade 5	6312	NO	Litho Box
142103	1,300	8"	49:1	30' x 5/16"	N/A	20' x 2"	1/4" x 2-1/2" Grade 5	6302	NO	Litho Box

All Horizon Brand Products single speed trailer winches are CE compliant. \*\*Maximum Mechanical Advance - Based on first layer of recommended line on the drum. For maximum efficiency, use only the amount of line required.



The F2® Winch addresses the need for attractive design in every element of a marine trailer. It complements the look of even high end boat and trailer combinations and continues the industry changing improvements in both performance and style of the Fulton F2® series of products.



## F2® TRAILER WINCHES

Part No.	Capacity	Gear Ratio	Handle Length	Strap	Strap Included	Mounting Hardware Included	Finish	Packaging	Unit Wt. Lbs.
<b>F2® SINGLE SPEED TRAILER WINCH</b>									
FW16000101	1,600	4.1:1	2 Position 6", 7"	20' x 2" w/Hook	YES	YES	Sharkskin™	Display Box	9.25
FW20000101	2,000	5.1:1	4 Position 6", 7", 8", 9"	20' x 2" w/Hook	YES	YES	Sharkskin™	Display Box	6.7

Make light work of heavy loads with Fulton brand two-speed winches. One fast speed for quick pull-in, a second low speed for increased mechanical advantage. Our shift lock design allows changing gears without moving the crank handle from shaft to shaft. Just lift the shift lock and slide the shaft into the desired gear position. Shift lock holds the shaft in gear. Neutral, free-wheel position allows quick line pay out without spinning the handle.

## TWO SPEED TRAILER WINCHES



Part No.	Cap.	Handle Length	Max. Mech. Adv**	Drum Storage		Strap Mfg. Bolt Sizes (Not Included)	Hub Size	Hand Brake	Strap Includ.	Cable Includ.	Pkg.
142400	2,000	10"	87:1	N/A	20' x 2"	N/A	1"	501210	NO	N/A	Litho Box
142410	2,600	10"	108:1	N/A	20' x 2"	N/A	1"	501210	YES	N/A	Bulk
142420	3,200	10"	79:1	100' x 7/32"	N/A	Cable only	1-3/4"	501210	N/A	NO	Litho Box
142430	3,700	10"	102:1	90' x 7/32"	N/A	Cable only	1-3/4"	Included	N/A	NO	Litho Box



Only winches that are shown to accommodate steel cable should be used with steel cable. Cable keeper kits are included with the winches specifying steel cable. Winches rated for steel cable have a larger drum hub to reduce or lessen chance of kinking or fraying.

## WINCH STRAPS AND CABLES



Part No.	Description	Packaging
501201	Winch Strap and Hook - Nylon web winch strap with hook, 2" x 20', 2,600 lb. maximum working load	Bulk
WC325 0100	Winch Cable and Hook - 3/16" x 25' galvanized cable, 4,200 lb. breaking strength	Clam Shell
WC750 0100	Winch Cable and Hook - 7/32" x 50' galvanized cable, 5,600 lb. breaking strength	Bagged

## WINCH ACCESSORIES

Part No.	Description	Packaging
1520	Trailer Wiring Kit for Superwinch EX1, X1,X2,X3 S3000 & S4000 Series Winches	Bulk
2008	Trailer Wiring Kit for Superwinch S5000, S6000, S9000 & X9 Series Winches	Bulk
2227A	Pulley Block for winches rated up to 8000 lbs.	Bulk